

# DISPLAY AND REGULATORY UNITS

panel,  
individual design  
current, voltage input



## PANEL

### GIA 2448 - display



- universal LED display unit built into a current loop
- power supply 12V or 24V supply adapter
- display 31 digit, 10mm high LED, accuracy +0,2%,
  - size 24x48mm

### GIR 600 - regulatory



- regulatory range: -1999+9999 digits
- input: 0-20mA, 4-20mA, 0-1V, 0-10V
- output: freely scalable 2-point regulator for normalized signals
- supply: 230V/50-60Hz; size 48x96mm
- case with IP 65 protection at additional charge

## BETWEEN CONNECTORS

### ZED 601 -display



- microprocessor display unit built into transducers current loop 4-20mA
- does not require any additional power supply
  - may be connected to any kind of transducer using connector DIN 43650

### GRA 420 - regulatory



- additional regulator/display unit into current loop
  - freely programmable by 3 buttons or infrared remote control
    - input: 4-20mA, 0-10V
    - display: 7mm high 4-digit

## SPECIFICATION:

### Display units:

Wide range of display units for majority of normalized signals (4-20mA, 0-20mA, 0-10V), with option of PC output.

Dimensions: from 24x48 up to 48x96mm. Design: into panel, flange, holder, adapter, connector DIN 43 650, etc.

### Regulatory units:

Integration of display function with regulation. Option of valve, vent, flap and other devices regulation. Easy setting, provision of high accuracy of regulation and control.

